

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

THIS PAGE BLANK (USPTO)


THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61M 15/00	A1	(11) International Publication Number: WO 00/06236 (43) International Publication Date: 10 February 2000 (10.02.00)
<p>(21) International Application Number: PCT/SE99/01243</p> <p>(22) International Filing Date: 8 July 1999 (08.07.99)</p> <p>(30) Priority Data: 9802648-7 30 July 1998 (30.07.98) SE</p> <p>(71) Applicant (for all designated States except US): MICRODRUG AG [CH/CH]; Landweg 1, CH-6052 Hergiswil (CH).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): NILSSON, Lars-Gunnar [SE/SE]; Esplanaden 15E, S-731 30 Köping (SE).</p> <p>(74) Agents: HEDBERG, Åke et al.; Aros Patent AB, P.O. Box 1544, S-751 45 Uppsala (SE).</p>		<p>(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: POWDER FEEDING DEVICE



(57) Abstract

The invention discloses a method and a device for de-agglomeration and electrostatic charging of a fine powder preferably intended for inhalation purposes. The electrostatic charging takes place by means of tribo, corona and/or inductive charging. The device according to the invention is particularly intended for being able to dose decomposed powder directly into the inspiration air for administering of, for instance, active pharmaceutical substances, alternatively provide a further dosing device (9) with electrostatically charged de-agglomerated powder for an even more controlled dosing of the substance into the inspiration air. De-agglomeration preferably takes place in that two rotating brushes (2, 3) containing powder are touching each other. The bristles are rubbed against each other and thereby decompose the powder agglomerates. The rotation speed of the brushes is suitably optimized to achieve the best possible result for different powder substances. The design of the brushes is further optimized for the substances, which are to be de-agglomerated and electrostatically charged prior to an administering step.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Powder feeding device**TECHNICAL FIELD**

The present invention relates to a device for feeding, de-agglomeration and electrostatic charging of a pulverized powder for inhalation by means of stationary or portable devices, whereby powder refers to active pharmaceutical substances and mixtures and specially treated preparations intended to be administered via the respiratory tract.

BACKGROUND AND PRIOR ART

Administering of medical powders today is performed in numerous ways. Within health care more and more is focussed on the possibility of dosing powder directly to the lungs by means of an inhaler to obtain an effective, quick and patient-friendly administering.

For the medical powders, being administered by means of an inhaler, to land in the lungs, the powder should have a grain size of 1 to 6 μm . A larger grain size will stick in the mouth and throat and a smaller grain size accompanies the expiration.

Powder having a small grain size will have a strong tendency of agglomerating, i.e. to get conglomerated. In the inhalers which are used today a large extent of the active substance is in the form of agglomerates when it is dosed and much powder therefore will stick in the upper respiratory tract. Different ways to de-agglomerate the powder have been developed and in most cases the inhalation air is utilized for decomposing the agglomerates.

It is also common to use carriers having a larger grain size onto which the fine powder is distributed. Upon inspiration the large grains will then stick in the oral cavity while the small grains are set free and proceed to the lungs. Certain manufacturers also use electrically driven propellers, piezo-vibrators and/or mechanical vibration to decompose the agglomerates. Thus, achieving a very large portion of individual particles in the inspiratory air is a

very important factor for obtaining a high degree of effectiveness upon inhalation.

5 In the Swedish patent publication SE 504 458 a device for an inhaler is disclosed, which utilizes a rotating drum as dosing device together with an electric field, which document hereby is incorporated by reference.

DESCRIPTION OF THE INVENTION

10 The present invention relates to a device for feeding, de-agglomeration and electrostatic charging of a fine powder, especially intended for inhalation purposes. The electrostatic charging takes place by means of tribo-, corona- and/or induction-charging. Charging of the powder is from now on referring to an electrostatic charging according to any of the mentioned ways or a combination of those. Particularly the device according to the present
15 invention is used for dosing powder directly to the inspiratory air, alternatively providing a dosing device with electrostatically charged de-agglomerated powder for a more controlled dosing to the inspiratory air, alternatively application to a carrier for further preparation and introduction to an inhaler or other device, e.g., a piece of plaster or the like.

20 The de-agglomeration takes place in that two rotating brushes containing powder are touching each other. The bristles of the brushes are pinched and scraped toward each other and thereby decomposing the powder agglomerates. At the same time also an electrostatic charging of the powder
25 may take place. The rotation speed of the brushes is optimized to achieve optimal results for different powder substances. The design of the brushes is preferably optimized for the substances to be de-agglomerated and electrostatically charged.

30 The choice of material then is adapted to the function the brushes are intended to have. If anti-static brushes are used, the main function is to decompose the agglomerates, while if another material is used, as for instance nylon, also a more pronounced electrostatic charging of the powder takes place.

As it is in practice impossible to obtain a complete de-agglomeration within the brushes, the dust delivered from the flipping device will contain a small amount of agglomerates. To have these agglomerates not to be integral in the powder to be dosed a separation must take place. This is arranged in a classification device, where a flipping takes place in the direction towards a reception device and where an electric field is present perpendicular to the direction of flipping. The kinetic energy, which is essentially larger for the agglomerates, will then convey the large particles to the reception device, while the small individual particles will be attracted to a dosing drum by means of the electric field. In this way only the individual particles will in practice be utilized for dosing.

The invention is defined by the independent claims 1 and 5 and different embodiments are defined by the dependent claims 2 - 4 and 6 - 14, respectively.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described in the form of a preferred illustrative embodiment and by means of the attached drawings wherein like reference numbers indicate like or corresponding elements and wherein:

FIG. 1 illustrates a flow chart of the path of powder through a device/an inhaler according to the present invention;

FIG. 2 illustrates a principal sketch of the feeding device in an illustrative embodiment for operation according to Fig. 1;

FIG. 3 illustrates another embodiment of the feeding device according to the present invention; and

FIG. 4 further illustrates an embodiment of the feeding device according to the present invention.

DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENT

Substances at first hand intended to be prepared are medical powders, but also other powders where an exact dosing of small quantities is needed may be considered. From now on in connection with the description of an illustrative embodiment powder will be used as a common word for all types of substances or preparations of substances, which shall be prepared.

FIG. 1 describes a method according to the present invention by illustrating in a schematic way the path of the powder through a dosing device according to FIG. 2. The powder is stored in a magazine 1. From the magazine, according to step 22, it is further fed to a decomposition device for de-agglomeration by means of a suitable device, e.g. in the form of a rotating plastic film or a brush. Superfluous powder is automatically brought back to the magazine 1 when the first brush 2 of the decomposition device is not able to receive more powder material. In this way a stable system is obtained, which maintains the powder feeding balance and thereby a possibility of even dosing will be obtained.

The de-agglomeration, which occurs in next step 23, takes place by smashing or decomposing the agglomerates by a suitably adapted device, which as was mentioned above, consists of two brushes in contact with each other according to the illustrative embodiment of the present invention. The powder is then, in step 24, released from the second brush 3 of the decomposition device in that it will, by means of a releasing member 5, be launched or flipped out from the second brush 3 in a way such that a dust cloud is formed. The dust cloud at this time consists to a larger part of individual particles, but an amount of agglomerates remains. To obtain a de-agglomeration as complete as possible a classification takes place in the next step 26.

Utilizing kinetic energy and an electric field for separating individual particles from agglomerated particles performs the classification, in step 26. For this to take place the powder particles must get a high velocity and be electrostatically charged when they leave the releasing device 5. The powder agglomerates being of relatively large size will have a high energy of motion

and these agglomerates therefore will proceed straight ahead. The small particles having a low energy of motion will more easily be able to be influenced by an electric field and change their direction of motion. Therefore an electric field is applied, the direction of which preferably being perpendicular to the direction of the motion the particles will obtain at the release from the brush
3.

The powder agglomerates travelling straight ahead will be taken care of by a reception means 7 for further conveying back to the magazine 1 or to the decomposition means. The individual particles forming a dust cloud are carried by the electric field, in a transfer step 32, to a dosing drum 9 for further preparation.

From the dosing drum 9 in the transfer step 32, dosing of powder to an air-stream takes place by means of an attracting electrode 14 or blowing off. The regulation of dosed amount of powder to the air, for instance, takes place by in a regulation step 34 varying a voltage and/or utilizing an electronically controlled filter 10. The dosing drum 9 is continuously cleaned from powder after that the dosing has taken place by its communication with the reception device 7. The powder which in this way is removed will be brought back via the reception device 7 to the rotating brushes 2 and 3 or the magazine 1, for instance by a further releasing device (not shown) corresponding to the device 5.

The result of the dosing, in step 36, will be an air flow, which contains a regulated amount of powder in the form of individual particles, which is a prerequisite to upon inhalation obtain a high efficiency for medical powders in the administering according to step 38.

An illustrative embodiment of the invention is disclosed in Figure 2. The magazine 1 is preferably round and contains, in the illustrative embodiment, a slowly rotating thin disc of plastics or a brush, which when it passes a bump in the magazine compartment, flips powder in the direction towards a first conveying and decomposing brush (decomposing means) 2, such that it all the

time has the same filling of powder. The magazine preferably is airtight and in communication with a compartment, which contains a moisture absorbing substance. In a further embodiment of the device an electric heating takes place to keep control of the climate within the apparatus.

The decomposition within the illustrative embodiment takes place by means of rotating brushes **2** and **3**, whereby design and selection of material is adapted to the characteristics of the powder. In another embodiment also other means than rotating brushes would be used. The rotational speed and the direction of rotation act on the powder to a high degree, and too high a speed can result in tendencies of melting and deposition within the apparatus.

The selection of material is important for a correct electrostatic charging of the powder to be obtained and an important part in the grading therefore is where the material is to be found in the tribo-electric series. In many cases is it also necessary to use conducting materials if it is desirable to avoid electrostatic charging. The following table illustrates the grading of some materials in the tribo-electric series.

Tribo-electric series

<i>Positively charged</i>
Glass
Nylon
Styrene
Rubber
Polyetene
PVC
Teflon
<i>Negatively charged</i>

Further relating to electric characteristics the materials may be divided into three groups:

- (1) Insulating materials, which are applicable for electrostatic charging , for instance by means of tribo-charging.

(2) Semi-conducting materials, which are not applicable for electrostatic charging, but being appropriate for certain portions of the apparatus, which should be set at a voltage potential.

(3) Conducting material as such necessary to use for avoiding electrostatic charging and to obtain a proper grounding.

The distance between the brushes is adjusted such that an optimal de-agglomeration is obtained. Normally it is preferable that the bristles of the brushes enters into each other between 0 and 3 mm. Just at the contact between the bristles agglomerated powder is rubbed to decompose and the brushes will in this way mainly contain individual particles.

To release the powder from the brush a releasing device **5** is used. An adequate releasing device, for instance, is a disc of appropriate material, which upon the rotation of the brush bends the bristles such that the powder is flipped when the bristles get straight again. A further alternative is to have an additional brush instead of the disc in the releasing device.

The dust from the rotating brush **3** in the releasing device goes out into a compartment where a classification takes place, i.e. a separation such that remaining agglomerated powder material can be brought back to the magazine **1** or to the decomposition means. This portion of the powder is carried to the reception device in form of an additional rotating brush **7**, while the decomposed powder as dust, which constitute individual particles, goes further to dosing by being distributed over a dosing drum **9**.

The dosing itself takes place in that an attracting electrode with an appropriate voltage attracts the powder grains from the dosing drum **9**. The potential of the attracting electrode is possible to vary between wide limits with an applied voltage normally between about 500 and 3000 volts. A flow of air, the inspiratory air, will drag away the small powder grains before those reach the attraction electrode. The amount of dosed powder can be governed by

connecting and disconnecting the voltage to the attraction electrode. Alternatively the dosing may be regulated in that an electronic filter is inserted between the dosing drum and the attraction electrode. A further alternative is that the airflow directly releases powder from the dosing drum, which is then positioned higher up in the device in direct contact with the airflow, which is illustrated in FIG. 3. The regulation in this case takes place by varying the electric field in the classification process corresponding to the step 26 of FIG. 1.

A normal method in connection to inhaler is that they are loaded with powder in the form of capsules. Disposable inhalers are loaded with one capsule while multi-use inhalers often are loaded with a strip containing several capsules. A further alternative therefore is that the dosing drum 9 is replaced by a powder dispenser (capsules) 9' which may be separate or be part of a strip in a way illustrated generally in FIG. 4. In this way the described feeding and dosing device advantageously may be used to in a simple way fill the capsules with an exact amount of powder, which according to the invention only consists of individual particles suitable for administering by inhalation. The device according to FIG. 4 presents as for the rest corresponding elements as in Figures 2 and 3.

The entire dosing apparatus then is designed such that no compartment is created where the powder may build up or rest. The selection of material here is also important for minimizing deposits. This further takes place in that walls and other parts are given the same or a higher potential and with same polarity as the electrostatically charged powder to create a repulse of the powder.

The method and the device have been disclosed by means of an illustrative embodiment, which however shall not be seen as limiting the scope of the invention, which instead is set forth by the appended claims.

CLAIMS

1 A method for feeding, decomposition and electrostatic charging of a powder intended for administering mainly by inhalation, **characterized by** the steps of:

5 decomposition of agglomerated powder into individual powder particles, which is achieved in that a first rotating means (2) and a second rotating means (3) are brought in engagement with each other, whereby the powder agglomerates, which are conveyed by the first rotating means is decomposed;

10 releasing of the decomposed powder from the second rotating means (3) by means of a releasing device (5);

separation of individual powder particles and remaining agglomerated powder by means of a classification device;

15 pick up of agglomerated powder by a reception device (7) for bringing that back to a magazine (1) or to the first rotating means (2);

transfer of the individual powder particles to a dosing drum 9; and

dosing of the individual powder particles controlled by means of an electric field bringing decomposed powder particles from the dosing drum (9) into an airflow.

20 2 The method according to claim 1, **characterized by** the further step of a charging of the powder at the rotating means (2 and 3) or at the releasing device (5) by selection of an appropriate material relative to the powder.

25 3 The method according to claim 1, **characterized by** the further step of air blowing off to further assist carrying out decomposed powder particles from the dosing drum (9) into the airflow (12).

30 4 The method according to claim 1, **characterized in** that the step of transferring individual powder particles to the dosing drum (9) is performed by means of an electrostatic field, obtained in that the dosing drum (9) is given an attracting electric potential in relation to the electric charge of the powder.

5. A device for feeding, decomposing and electrostatic charging of a powder intended for administering mainly by inhalation, **characterized in** that it comprises

a magazine (1) for powder to be administered;

a first rotating means (2) in communication with the magazine (1)

a second rotating means (3) in communication with the first rotating means (2), whereby the first means and the second means form a de-agglomeration zone where present powder agglomerates are decomposed into individual powder particles suitable for administering;

a releasing means (5) for releasing decomposed powder from the second rotating means (3);

a third rotating means (7) for bringing agglomerates not decomposed back to the magazine (1) or to the first rotating means (2); and

a dosing means (9) for reception of the decomposed powder for administering.

6. The device according to claim 5, **characterized in** that the de-agglomeration zone is constituted by a first and a second rotating brush (2,3), whereby bristles of the two brushes are brought in engagement with each other and in the communication between the bristles agglomerated powder will be rubbed to decompose and the second brush (3) will essentially contain individual powder particles.

7. The device according to claim 5, **characterized in** that a electrostatic charging of the powder takes place by means of tribo or corona or inductive charging or a combination of these by selection of an appropriate material in relation to the tribo-electric series and in relation to applied voltages in the feeding device.

8. The device according to claim 7, **characterized in** that the material of the device is selected such that tribo, corona and/or inductive charging of the powder will be governed by externally applied and controlled fields.

9. The device according to claim 5, **characterized in** that the magazine for the powder comprises a slowly rotating disc or brush, which when it passes a bump flips powder towards the adjacent rotating means (2).

5 10. The device according to claim 5, **characterized in** that it furthermore is provided with a container for a dehydrant to obtain a controlled climate regarding level of moisture.

10 11. The device according to claim 5, **characterized in** that it is provided with an electrical heating device for control of climate in the feeding and decomposition compartments.

15 12. The device according to claim 5, **characterized in** that within the device a compartment is arranged for the ready-made powder in form of dust for later handling.

20 13. The device according to claim 5, **characterized in** that the walls of the device are made of a conducting or semi-conducting material having an electric potential of the same sign as the charged powder to minimize deposits.

14. The device according to claim 5, **characterized in** that the dosing means (9') is designed as a powder technical source in the form, for instance, of a strip for a later mounting in a separate inhalation device.

1/4




Figure 1

2/4




Figure 2

3/4




Figure 3

4/4




Figure 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/01243

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61M 15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5655523 A (P.D. HODSON ET AL), 12 August 1997 (12.08.97), column 10, line 14 - line 47 --	1-14
A	WO 9700704 A1 (LARS GUNNAR NILSSON), 9 January 1997 (09.01.97), page 5, line 1 - line 29 --	1-14
A	JP 61157335 (IRIE KABEZAI KK) 1986-07-17(abstract) World Patents Index (online). London, U.K.: Derwent Publications, Ltd. (retrieved on 1999-10-12). Retrieved from: EPO WPI Database, DW8635, Accession No. 86-228335 -- -----	6

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

12 October 1999

Date of mailing of the international search report

14 -12- 1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lotta Gunnarsson/AE

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

28/09/99

International application No.
PCT/SE 99/01243

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5655523 A	12/08/97	DE 69027319 D,T	21/11/96
		EP 0470154 A,B	12/02/92
		SE 0470154 T3	
		AT 138814 T	15/06/96
		AU 643435 B	18/11/93
		AU 644790 B	23/12/93
		AU 5539590 A	29/11/90
		AU 5558890 A	29/11/90
		CA 2050298 A	29/10/90
		CA 2058764 A	29/10/90
		DE 69027679 D,T	14/11/96
		DK 470154 T	21/10/96
		DK 472598 T	29/07/96
		EP 0472598 A,B	04/03/92
		SE 0472598 T3	
		EP 0705614 A	10/04/96
		ES 2087911 T	01/08/96
		ES 2091825 T	16/11/96
		HK 1006546 A	00/00/00
		JP 4504671 T	20/08/92
		JP 5501505 T	25/03/93
		NZ 233486 A	26/05/95
		NZ 248275 A	26/05/95
		US 5619984 A	15/04/97
		US 5740793 A	21/04/98
		WO 9013327 A	15/11/90
		WO 9013328 A	15/11/90
WO 9700704 A1	09/01/97	AU 697654 B	15/10/98
		AU 6247496 A	22/01/97
		CA 2224929 A	09/01/97
		CN 1192703 A	09/09/98
		EP 0836496 A	22/04/98
		JP 11508161 T	21/07/99
		SE 504458 C	17/02/97
		SE 9502262 A	22/12/96

THIS PAGE BLANK (USPTO)